



ARL-TN-0782 • SEP 2016



Android: Call C Functions with the Native Development Kit (NDK)

by Hao Q Vu

Approved for public release; distribution is unlimited.

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.



Android: Call C Functions with the Native Development Kit (NDK)

by Hao Q Vu

Sensors and Electron Devices Directorate, ARL

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>					
1. REPORT DATE (DD-MM-YYYY) September 2016		2. REPORT TYPE Technical Note		3. DATES COVERED (From - To) 02/2016–05/2016	
4. TITLE AND SUBTITLE Android: Call C Functions with the Native Development Kit (NDK)				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Hao Q Vu				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) US Army Research Laboratory ATTN: RDRL-SES-P 2800 Powder Mill Road Adelphi, MD 20783-1138				8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TN-0782	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT The Android Native Development Kit (NDK) provides a Java Android application a simplified mechanism to call embedded C native codes, which are used to increase the performance of a computationally intensive application. This step-by-step guide is intended to assist programmers with how to attach an NDK plugin to an Android Integrated Development Environment and how to call C functions from a Java application.					
15. SUBJECT TERMS Android, NDK, Native Development Kit, C callable, Java Native Interface, JNI, Java, C/C++					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 20	19a. NAME OF RESPONSIBLE PERSON Hao Q Vu
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (Include area code) 301-394-5324

Contents

List of Figures	iv
1. Introduction	1
2. Android Studio IDE	1
3. Android NDK Package	1
3.1 Method 1	1
3.2 Method 2	2
4. Configure NDK with Android Studio IDE 1.5.1	2
5. Create an Android Application	6
6. Final Build and Run Android Application	13
7. Conclusion	13
Distribution List	14

List of Figures

Fig. 1	Create Tool window.....	3
Fig. 2	“Javah” path.....	3
Fig. 3	Environment path.....	5
Fig. 4	NDK-BUILD CLEAN configuration	6
Fig. 5	Android application	6
Fig. 6	Java codes to add 2 integer numbers.....	7
Fig. 7	Native library Java class	7
Fig. 8	JNI directory	8
Fig. 9	JNI header file.....	9
Fig. 10	Create a C source file.....	10
Fig. 11	Java native C functions	10
Fig. 12	Android.mk makefile	11
Fig. 13	Application.mk makefile.....	12

1. Introduction

With its compact form factor, portability, low power consumption, and increasing processing power, the Android mobile platform is gaining popularity as a replacement for traditional desktop or laptop computers as a processing platform. Most digital signal processing algorithms developed at the US Army Research Laboratory are written in the C programming language to provide sufficient processing power to satisfy typical processing and performance requirements. Typical applications developed for the Android mobile platform are written in Java. Therefore, to achieve maximum speed, there is a need to bridge Java-based applications to native C applications. Fortunately, a combination of the Android Native Development Kit (NDK) and the Java Native Interface (JNI) provides such a mechanism.

NDK is a toolset that allows users to build C/C++ functions into a static or dynamic library or let the existing prebuilt library be called from an Android application. JNI defines a way for managed code written in Java to interact with native C/C++.

This guide is intended to take programmers through adding an NDK package into an Android Studio Integrated Development Environment (IDE), to building a simple Android application that calls a C function to add 2 integer values received from the user screen.

2. Android Studio IDE

This guide assumes the user has already downloaded the Android Studio IDE and has an extensive working knowledge of this development package. As of the writing of this report, the version of Android Studio IDE was 1.5.1.

3. Android NDK Package

The Android NDK package can be downloaded via either of the following methods.

3.1 Method 1

The latest version of the NDK package for one's operating system can be downloaded directly from "developer.android.com/ndk/downloads/index.html".

Expand the package once it has downloaded.

3.2 Method 2

Download the NDK package directly from Android Studio IDE:

- 1) Select the “Tools” tab.
- 2) Select “Android->SDK manager”.
- 3) Select “Appearance->System Settings->Android SDK”.
- 4) Select the “SDK Tools” tab.
- 5) Check the box labeled “Android NDK”.
- 6) Select “Apply”.

Wait for the package to be added into the Android Studio IDE. The downloaded package can be found at “~/Library/Android/sdk/ndk-bundle”.

4. Configure NDK with Android Studio IDE 1.5.1

Perform the following steps to configure the NDK with Android Studio IDE, version 1.5.1:

- 1) Set up the Android NDK location:
 - a) Select “File->Project Structure”.
 - b) Select “SDK Location”.
 - c) If Method 1 was chosen, enter the NDK location of where the downloaded NDK package was expanded. If Method 2 was chosen, then Android Studio will automatically fill in the NDK location.
- 2) Add the JAVA_HOME, NDK-BUILD, and NDK-BUILD CLEAN paths:

JAVA_HOME is a tool provided by Java SE to generate a C header and the source files that are needed to implement native methods. Refer to <http://docs.oracle.com/javase/7/docs/technotes/tools/windows/javah.html> for a detailed description.

- 3) Configure the JAVA_HOME path:
 - a) Select “Tools->Android->SDK Manager”.
 - b) Select “Tools->External Tools”.
 - c) Select “+” at the bottom of the right pane.
 - d) The “Create Tool” window (Fig. 1) will pop up.




Fig. 1 Create Tool window

e) Enter the following to create a path for “javah”, as shown in Fig. 2.




Fig. 2 “Javah” path

Notes:

- *Program*: This needs to point to where the JAVAH application is located on the host.
- *Parameters*: The parameters are set to `-classpath $Classpath$ -v -jni $FileClass$`
 - `-classpath` specifies the path for “javah” to look for classes
 - `-v` verbose
 - `-jni` tells “javah” to create an output file with JNI-style native method function prototypes
- *Working directory*: All the required files needed to create a C callable object are located in the “jni” directory.

NDK-BUILD is a shell script used to call a GNU “make” 3.81 or later. Use the following steps to configure it:

1) Configure the NDK-BUILD path:

- a) Select “Tools->Android->SDK Manager”.
- b) Select “Tools->External Tools.
- c) Select “+” at the bottom of the right pane.
- d) The “Create Tool” window (see Fig. 1) will pop up.
- e) Enter the following to create an environment path for NDK-BUILD, as shown in Fig. 3:
 - *Program*: This points to the location to where NDK-BUILD is located.
 - *Parameters*: Leave blank.
 - *Working directory*: This points to where all the Java files are located.




Fig. 3 Environment path

NDK-BUILD CLEAN is used to remove all previously generated binaries. Use the following steps to configure it:

- 1) Configure the NDK-BUILD CLEAN path:
 - a) Follow the same steps as if configuring the NDK-BUILD path, except the parameter is set to “clean”.
 - b) The final NDK-BUILD CLEAN configuration screen should look like Fig. 4.




Fig. 4 NDK-BUILD CLEAN configuration

5. Create an Android Application

This guide assumes that the user is well versed in using the Android Studio IDE to create an Android application. Therefore, a step-by-step guide on how to create an Android application has not been included. A simple Android application is provided as an example highlighting the functionality outlined in this report.

A newly created Android application is shown in Fig. 5.




Fig. 5 Android application

The user can then add the ability to read in 2 integer numbers, as shown in Fig. 6.




Fig. 6 Java codes to add 2 integer numbers

To do this, the user must set up a sequence to call a C function from an Android application:

- 1) Create a native library Java class as shown in Fig. 7. This class resides in the “src “directory. This class includes an Android system call to load the library that was written in C and all the C function prototypes.




Fig. 7 Native library Java class

2) Create the JNI directory as shown in Fig. 8, to store all related C source files and H header files:

a) Select “app->New->Folder->JNI folder”.

b) Select “Finish”. The “jni” directory should appear under the “app” directory.




Fig. 8 JNI directory

3) Create the JNI header file using the external tool JAVAH, as shown in Fig. 9:

a) Select “NativeLib->NDK->javah”:

Based on the Java class created earlier, a header file will appear under the “jni” directory that has the following naming convention.

- PackageName: *com_example_haovu_addtwonumbers*
- Followed by the NativeJavaClassname: *NativeLib*
- Followed by the *.h* extension
- Example: *com_example_haovu_addtwonumbers_NativeLib.h*

b) The newly created header file contains the Java native function prototypes with the following format:

- *JNIEXPORT*
- The function return type

- *JNICALL*
- *Java*
- Followed by the PackageName
- Followed by the NativeJavaClassname
- Followed by the FunctionName
- Example: *JNIEXPORT jint JNICALL Java_com_example_haovu_addtwonumbers_NativeLib_add (JNIEnv *, jobject, jint, jint)*




Fig. 9 JNI header file

- Under the “jni” directory, create a C source file (NativeLib_C.c), as shown in Fig. 10, to implement the native C functions:
 - Select “jni->New->C/C++ Source File”.
 - Enter the filename and type.
 - Select “OK”.




Fig. 10 Create a C source file

d) Implement the Java native C functions as shown in Fig. 11.




Fig. 11 Java native C functions

e) Modify “build.gradle (Module:app)”:

i) Inside the “defaultConfig” section, add the following pseudo code:

```
sourceSets {  
    main{  
        jni.srcDirs = []  
        jniLibs.srcDir “src/main/libs”  
    }  
}
```

f) Create an “Android.mk” makefile, shown in Fig. 12, under the “jni” directory to determine how to build the C code:

i) Select “jni->New->File”.

ii) Enter “Android.mk” as the filename.




Fig. 12 Android.mk makefile

g) Create the “Application.mk” makefile, shown in Fig. 13, under the “jni” directory to tell the NDK what architecture it should build the shared library for:

i) Select “jni->New->File”.

ii) Enter “Application.mk” as the filename.




Fig. 13 Application.mk makefile

Note: This application.mk requests the NDK to build a shared library for all supported architectures. The following details how to build a shared library:

1) Select “app->NDK->ndk-build”:

- A “libs” directory that stores the shared library for all the architectures is automatically created.
- All the supported architecture directories are created.
- Under each architecture directory, a shared library for that particular architecture can be found.

6. Final Build and Run Android Application

Perform the following steps to create the final build and run the Android application:

- 1) Select “Build->Make Project”.
- 2) Select “Run-> Run ‘app’”.

7. Conclusion

This guide summarizes all the necessary mechanisms and steps to guide a novice Android application developer to build an Android application that is capable of handling a high-intensive computation requirement.

1 DEFENSE TECHNICAL
(PDF) INFORMATION CTR
DTIC OCA

2 DIRECTOR
(PDF) US ARMY RESEARCH LAB
RDRL CIO L
IMAL HRA MAIL & RECORDS
MGMT

1 GOVT PRINTG OFC
(PDF) A MALHOTRA

8 US ARMY RSRCH LAB
(PDF) RDRL SES P
C REIFF
D GONSKI
H VU
L SIM
M SCANLON
S TENNEY
W ALBERTS II
RDRL SES S
B MAYS